

# Chair Frame

by Catherine Mather (c) 2004

Care must be taken when handling the frame, there are many sharp edges that are best sanded with 220 garnet sand paper( by hand)  
Where you are going to gild ,paint or crackle paint the frame a good base coat of gesso will help your paint flow well over the resin frame

Please Note Handel the frame with as much care as you would handle porcelain .  
Finishers for Chaise Lounge Frame

Gild

- #Base coat Gesso (Jo Sonja's) .
- # 2 Red base coat (Delta Renaissance Italian Red Base Coat)
- # Gold Leaf Adhesive Size
- # Gild with composition gold leaf
- #Satin seal

Paint Wood Finish

- #Base coat Gesso(Jo Sonja's)
- # Medium brown acrylic paint full cover
- # Dark brown acrylic paint dry brushed on lightly to highlight detail
- # Satin seal

Crackle Paint

- #Base coat Gesso(Jo Sonja's)
- #Colour base coat ( gold )
- # Crackle medium
- #Top coat ( cream )

*Cat & Co*

31 Hurt Pde Unanderra N.S.W 2526  
Ph/ 0242713302 Email artist @catnco.com  
[www.catnco.com](http://www.catnco.com)

# Sewing Instructions

## Chair Covers

Fabric 80cm x 18 cm

Foam 30cm x 16 cm

Cardboard 40cm x 16 cm

Braid narrow 2m

Cut all pieces as marked on pattern

1 Chair seat in cardboard

1 Chair rest front in 3mm foam

1 Chair rest front in cardboard

1 Chair rest back in 3mm foam

1 Chair rest back cardboard

1 Chair seat in 3mm foam

Cut all fabric pieces following the grain (arrows)

1 Chair rest back in top fabric

1 Chair rest front in top fabric

1 Chair seat top in top fabric

Chair cushion 1 set

Seat

\*Glue cardboard chair seat in to position on top of slats

\* Glue foam seat on top of cardboard

\* Glue fabric chair top over foam and on to frame, trimming where necessary around arm neaten raw edge of fabric with braid

\* Stitch pillow together, leaving an opening for filling. turn through and fill with a 200g of plastic or glass pellets (as used for filling dolls & bears)

place a small amount of fibre fill (Dacron) on top of beads, stitch opening closed. Hand stitch braid around seam of pillow add tassels on each corner of the pillow

Chair Rest Front

\* Trim seam allowance away from edge of cardboard rest front .(in side line of pattern)

\*Check that it fits neatly up against slats. glue foam to card trim a way excess.

\*Cover foam and card board with top fabric , clipping seams as marked and gluing seam allowance to under side of cardboard ,to give a neat edge

\* Glue in to position on front rest . Trim edge with braid

Chair Rest Back

\* Trim seam allowance away from edge of cardboard rest back.(inside line of pattern)

\*Check that it fits neatly up against slats.

\*Cover card board with top fabric , clipping seams as marked and gluing seam allowance to under side of cardboard ,to give a neat edge

\* Glue in to position on chair back rest . Trim edge with braid

*Cat & Co*

[www.catnco.com.au](http://www.catnco.com.au)

[artist@catnco.com](mailto:artist@catnco.com)



# *Chair Pattern*

*Cat & Co*

31 Hurt Pde Unanderra

N.S.W 2526

Ph/ 02 42 713302

[www.catnco.com](http://www.catnco.com)

email [artist@catnco.com](mailto:artist@catnco.com)



